

Test tube shaker TTS 2

- ☒ **Universal shaker for test tubes and small vessels**
- ☒ **Continuous operation or automatic mode of operation by pressure on the top attachment**
- ☒ **A large selection of attachments allows for an extensive range of applications**

Shaking motion:	orbital
Shaking orbit:	Ø 4,5 mm
Perm. agitation weight (with attachment):	0,5 kg
Motor rating input / output:	30 / 23 W
Permissible ON-time:	100 %
Speed range (infinitely adjustable):	0 - 2.500 rpm
Speed display:	scale / analog
Dimensions (W x D x H):	115 x 225 x 60 mm
Weight:	3,5 kg
Protection class acc. to DIN EN 60529:	IP 21



MS 1.34 Id-Nr. L001830

Test tube insert MS 1.34

No pre-drilled holes. Any number of holes may be drilled.



MS 1.33 Id-Nr. L001860

Test tube insert MS 1.33

4 holes, Ø 15 mm



MS 1.32 Id-Nr. L001850

Test tube insert MS 1.32

6 holes, Ø 10 mm



MS 1.31 Id-Nr. L001840

Test tube insert MS 1.31

14 holes, Ø 8 mm

IKA®-WERKE GMBH & CO.KG

IMLAB bvba

Tel 0032 16 73 55 72
Fax 0032 16 73 55 87

www.imlab.com
xavier.wispenninckx@skynet.be

Subject to technical changes. Indications not binding for delivery.